



COLOR-PAVE LTD

MANUFACTURERS OF SWISS-SEAL SEALERS AND CLEANERS

BLOCK PAVING CLEANING AND SEALING – SOLVENT SEAL

THE PROCESS OF WEEDING, CLEANING AND SEALING CONCRETE BLOCK PAVING BLOCKS

TECHNICAL SUPPORT

Unit 4, Leachfield
Industrial Estate, Green
Lane West
Garstang, Preston
Lancashire
PR3 1PR

sales@color-pave.co.uk

WITH THE WEEDS GROWING AND IN SITU APPLY OUR GROUNDKILL WEEDKILLER LIBERALLY WITH A WATERING CAN OVER THE WHOLE AREA OF THE CONCRETE BLOCK PAVING

Leave for 10 – 14 days

At this point apply our Block Paving Cleaner with a sprayer, roller or brush to the surface area of the Concrete Block Paving

Leave 24 hours then jet wash clean the surface area of the Concrete Block Paving then leave to dry

When the Concrete Block Paving are completely dry and the conditions for the day are warm enough (10°C) and the forecast is clear for the day replace the kiln dried sand into all the joints making sure that any excess is removed from the top of the blocks and the top of the joints

Apply the High Solids Block Paving Sealer with our adapted sprayer evenly, two coats if the block are old and more porous. (Roller and Brush can be used but movement of sand is an issue)

Leave 4 hours to walk on and 24 hours to drive on.

This process will last 2.5 – 3 years and will then need resealing