



COLOR-PAVE LTD

MANUFACTURERS OF SWISS-SEAL SEALERS AND CLEANERS

TARMAC DRIVE AND PATIO CLEANING AND SEALING

THE PROCESS OF CLEANING AND SEALING TARMAC DRIVEWAYS AND PATIOS WITH COLOURED SOLUTIONS

TECHNICAL SUPPORT

Unit 4, Leachfield
Industrial Estate, Green
Lane West
Garstang, Preston
Lancashire
PR3 1PR

sales@color-pave.co.uk

1. **JET WASH THE WHOLE AREA WITH COLD WATER ONLY THEN LEAVE TO DRY POSSIBLY NEXT DAY.**
2. **WHEN COMPLETELY DRY APPLY OUR TARMAC CLEANER USING A FINE ROSE WATERING CAN OR LIGHT PRESSURE SPRAYER. ENSURE THE OVERSPRAY IS CONTROLLED**
3. **LEAVE FOR AT LEAST TWO HOURS BEFORE PRESSURE WASHING THE AREA**
4. **WHEN DRY APPLY OUR TARMAC RENOVATOR WITH A DEEP PILE ROLLER, GOING BACK OVER PARTS TILL A UNIFORM COLOUR**
5. **WITH OLDER AND MORE POROUS DRIVES OR PATIOS A SECOND COAT MAY NEED TO BE APPLIED AS ABOVE TO GIVE IT THE SHINE AND LUSTER**
6. **LEAVE FOR 4 HOURS TO WALK ON AND 24 HOURS TO DRIVE ON**
7. **THE COATING WILL LAST 2.5 – 3 YEARS BEFORE A NEW COAT IS REQUIRED**