



COLOR-PAVE LTD

MANUFACTURERS OF SWISS-SEAL SEALERS AND CLEANERS

TINTED IMPRINTED CONCRETE CLEANING AND SEALING

TECHNICAL SUPPORT

Unit 4, Leachfield
Industrial Estate, Green
Lane West
Garstang, Preston
Lancashire
PR3 1PR

sales@color-pave.co.uk

THE PROCESS OF CLEANING AND SEALING IMPRINTED CONCRETE DRIVEWAYS AND PATIOS WITH COLOURED SOLUTIONS

- 1 JET WASH THE WHOLE AREA WITH COLD WATER ONLY THEN LEAVE TO DRY POSSIBLY NEXT DAY.**
- 2 WHEN COMPLETELY DRY APPLY IF NECESSARY, CRACK REPAIR KIT AS EXPLAINED WITH THE RELEVANT COLOUR, LEAVE FOR AT LEAST 4 HOURS**
- 3 THEN WITH OUR ROLLER OR OUR SPRAYER APPLY THE TINTED SEALER TO THE AREAS THAT NEED IT MOST FIRST. LEAVE FOR AT LEAST 4 HOURS**
- 4 THEN WITH OUR ROLLER OR OUR SPRAYER APPLY THE TINTED SEALER ONE EVEN COAT OF THE COLOURED SOLUTION TO THE WHOLE AREA. LEAVE FOR AT LEAST 4 HOURS.**
- 5 WITH OLDER AND MORE POROUS DRIVES OR PATIOS A SECOND COAT MAY NEED TO BE APPLIED AS ABOVE TO GIVE IT THE SHINE AND LUSTER**
- 6 LEAVE FOR 4 HOURS TO WALK ON AND 24 HOURS TO DRIVE ON**
- 7 THE COATING WILL LAST 2.5 – 3 YEARS BEFORE A NEW COAT IS REQUIRED**